

## INSTALLATION

### CTI SEALANT & ADHESIVE



CTI Construction Sealant and Adhesive uses a unique TRIBRID® Technology for a superior bond when compared to standard hybrid polymers. Available in 8 colours, please refer to the colour chart below for recommended colour options when using with Cladco Roofing Sheets.

CTI COLOUR	ROOFING
Anthracite	Anthracite Slate Blue Merlin Grey Graphite Grey
Beige	-
Black	Black
Brown	Vandyke Brown
Grey	Goosewing Grey Light Grey Galvanised
Oak	Copper Brown
Clear	Juniper Green Chestnut Moorland Green Olive Green
White	White

CTI Sealant & Adhesive benefits include:

- Excellent colour retention
- UV resistant
- Works in wet and dry conditions, or underwater
- Odourless
- Does not shrink
- Contains no solvents
- No isocyanates
- Moderate resistance to fungus
- Environmentally compliant
- Excellent chemical resistance

SPECIFICATIONS	
Material	TRIBRID® Polymer
Full Cure Time	12hrs (per 2-3mm bead size)
Size	290ml
Application Temperature	+5°C to +40°C

COLOURS				
	Anthracite	Beige	Clear	Oak
	Black	Brown	Grey	White

**PLEASE NOTE** - We advise using the correct type of glove (with level 5 cut resistance) when handling or moving steel Sheets and Flashings. Extra care should always be taken when working with metal products.



01837 659901 [info@cladco.co.uk](mailto:info@cladco.co.uk)  
[www.cladco.co.uk](http://www.cladco.co.uk)

Beardown Road, Exeter Road Industrial Estate, Okehampton EX20 1UA

