

# Nordic Ridge Flashing Galvanised



Ridge flashings are used at the apex of the roof to join the two sides together. At Cladco, our ridge flashings are folded to a 130-degree internal angle and will flex 10 – 15 degrees either way, dependent on the angle of your roof. Ridges are a major component in any profiled clad apex roof, and they will enhance the aesthetics of any building, especially in galvanised.

## Roof Edge Flashing for you Roofing

Here at Cladco Profiles, we try to accommodate your needs wherever possible. While our ridge flashings are manufactured as a 3-metre length, if you provide us with your dimensions, we'll do our best to get you the exact sizes you need. Each Ridge Flashing is folded to a 130-degree internal angle and will flex 10-15 degrees each way. Our Polyester Paint Coated Ridge flashings come with a safety welt to increase the strength of the material. For custom flashings please visit our custom flashings page.

**Please note:** The 195 x 195 flashings give a coverage of 195 x 195 due to the 8mm welt.

SPECIFICATIONS	
Length	3 metres
Sizes available	195 x 195mm
Angle	130° internal angle
Overlap	Allow 150mm

**PLEASE NOTE** – Extra care should always be taken when handling metal sheets and flashings we advise using the correct type of Glove when handling or moving metal sheets and flashings.



01837 659901 [info@cladco.co.uk](mailto:info@cladco.co.uk)  
[www.cladco.co.uk](http://www.cladco.co.uk)

Beardown Road, Exeter Road Industrial Estate, Okehampton EX20 1UA