


130° Ridge Flashings Polyester



Ridge pieces are used at the apex of the roof to join the two sides together. Cladco polyester paint coated flashing ridges are folded to a 130-degree internal angle and will flex 10 - 15 degrees either way, dependent on the angle of your roof. Metal roof flashing ridges are a major component in any profiled clad apex roof and are available in a range of colours and finishes to match our roofing sheets. Polyester paint coated ridge flashing will enhance the aesthetics of any building, providing the perfect finish.

Polyester Paint Coated Ridge for your Roofing

Here at Cladco Profiles, we try to accommodate your needs wherever possible. While our ridge flashings are manufactured as a 3-metre length, if you provide us with your dimensions, we'll do our best to get you the exact sizes you need. Each Ridge Flashing is folded to a 130-degree internal angle and will flex 10-15 degrees each way. Our Polyester Paint Coated Ridge flashings come with a safety welt to increase the strength of the material. For custom flashings please visit our custom flashings page.

Please note: The 150 x 150 flashings give a coverage of 142 x 142 due to the 8mm welt.
The 200 x 200 flashings give a coverage of 192 x 192 due to the 8mm welt.

SPECIFICATIONS	
Length	3 metres
Sizes available	150mm x 150mm or 200mm x 200mm
Angle	130° internal angle
Overlap	Allow 150mm
Colours available	Black, Juniper Green, Slate Blue, Grey & White

PLEASE NOTE - Extra care should always be taken when handling metal sheets and flashings we advise using the correct type of Glove when handling or moving metal sheets and flashings.

☎ 01837 659901 ✉ info@cladco.co.uk

WWW.CLADCO.CO.UK

Beardown Road, Exeter Road Industrial Estate, Okehampton EX20 1UA