



Cladco Profiles Ltd.

INTERNAL SUPPORT TESTING IN ACCORDANCE WITH THE
BRITISH STANDARD EN 1993-1-3:2006



DOCUMENT REFERENCE: DR-5897

PROJECT FILE REFERENCE: P10313

Prepared for: Cladco Profiles Ltd.

Stanhope House, 9-10 Fore Street, Holsworthy, Devon, EX22 6DT

Unit D4, Poole Hall Business Park, Poole Hall Road, Ellesmere Port, Cheshire, CH66 1UA, United Kingdom

T: +44 (0) 1244 794 104 F: +44 (0) 1244 794 204

E: Info@sts-group.co.uk

Offices Located at: Chester | Ellesmere Port

Website: <https://www.sts-group.co.uk>



Registered and Insured to carry out Load Testing, Structural Monitoring and Various Inspection works within the UK and Europe. Approved with ConstructionLine Gold; Memberships to BSI and ASTM plus RoSPA, IPAF and the IATP in England and Wales. BSI ISO Compliant Management Systems – 9001:2015 | 14001:2015 | 45001:2018.

STS-UK Group is a trading name of Specialist Technical Services (U.K) Limited, Registered in England and Wales No.: 09524652. VAT No.: GB 219 4694 80

Registered Address: 8 Hunters Crescent, Tarvin, Chester, Cheshire, CH3 8EY, United Kingdom

Document Title	P10313 – DR-5897 – Internal Support Testing Report v2.0
Author	Mr. Benjamin Cartwright, Specialist Technical Services (U.K) Limited
Client	Cladco Profiles Ltd.
Document Status	First Draft for Issue
-----	-----

Revision History

Version	Date	Reason for Issue
v0.0	17/04/2025	Draft for Internal Review
v1.0	17/04/2025	First Issue for Comment
V2.0	12/05/2025	Final Issue

Distribution List

Name	Role
Miss Amy Lett	Customer Support & Quality Manager
-----	-----
-----	-----
-----	-----

This document has been prepared by a division, subsidiary or affiliate of Specialist Technical Services (U.K) Limited, herein known as ("STS-UK") in it's professional capacity as a Testing House in accordance with the terms and conditions of STS-UK's instruction with the commissioning party (the "Client"). Regard should be had to those terms and conditions when considering and/or placing any reliance on this document. No part of this document may be copied or reproduced by any means without prior written permission from STS-UK by means of an authorised person. If you have received this document in error, please destroy all copies in your possession or control and notify STS-UK.

Any advice, opinions or recommendations within this document (a) should be read and relied upon only in the context of the document as a whole; (b) do not, in any way, purport to include any manner of legal advice or opinion; (c) are based upon the information made available to STS-UK at the time of this document and on current UK standards, codes, technology and practices as at the date of this document. It should be noted, and it is expressly stated that no independent verification of any of the documents or information supplied to STS-UK has been made. No liability is accepted by STS-UK for any use of this document. Following final delivery of this document to the Client, STS-UK will have no further obligations or duty to advise the Client on any matters, including development affecting the information, recommendations or advice provided within this document.

This document has been prepared for the exclusive use of the Client and unless otherwise agreed in writing by STS-UK, no other party may use, make use of or rely on the contents of this document. Should the Client wish to release this document to a third party, STS-UK may, at it's discretion, agree to such release provided that (a) STS-UK's written agreement is obtained prior to such release; and (b) by release of this document to the third party, that third party does not acquire any rights, contractual or otherwise, whatsoever against STS-UK and STS-UK, accordingly, assume no duties, liabilities or obligations to that third party; and (c) STS-UK accepts no responsibility for any loss or damage incurred by the Client or for any conflict of STS-UK's interests arising out of the Client's release of this document to the third party.

* END OF PAGE *

CONTENTS

1. INTRODUCTION	4
2. METHODOLOGY	4
3. RESULTS.....	5
4. CONCLUSION	7

Appendix A – Photographic Evidence

* END OF PAGE *

1.0 Introduction



Specialist Technical Services (U.K) Limited, herein known as STS-UK Group were commissioned by Cladco Profiles Ltd. to undertake a series of internal support tests on C and Z purlins with a variety of different lengths and heights. All testing was carried out by STS-UK's own direct labour force. The purpose of the testing was to attain results and findings that could be analysed to determine the resistance of the purlins that is continuous over two or more spans. All systems tested were done so in accordance with the British Standard EN 1993-1-3:2006. Each component was briefly surveyed for damage before and after testing was carried out.

The testing was carried out at the following address:

Site Address: Unit 4, Poole Hall Business Park, Poole Hall Road, Ellesmere Port, CH66 1UA

Dates of Testing: 2nd to the 8th of April 2025

2.0 Methodology

Internal Support Testing on Torsionally Restrained Beams

The test set-up in figure 1 was used for all testing undertaken.




Figure 1 – Internal Support Test Set-Up

Supports **A** and **E** were roller supports with brackets either side of the purlins to minimise horizontal rotation whilst under load. Additionally, there were brackets placed at point **C** to further reduce lateral displacement.

Displacement was measured at points **B**, **C** and **D**. Points **B** and **D** were located a distance *e* from the end of the purlin which was selected to be 20% of the total length (*L*) of the purlin.

Test span *s* was selected to be the length of the purlin minus 50mm from either side of the purlin.

Testing continued past peak load until the applied load reduced to by 10% of its original value.

The load **F** was applied using a 10 Tonne hydraulic ram and all displacements were measured using highly accurate draw wire displacement sensors.

For each test, a support moment **M** was calculated. Using the following equation.

$$M = \frac{s R}{4}$$

Figure 2 – Moment Equation

* END OF PAGE *

3.0 Results



Upon a brief visual survey of the barrier[s] to be tested, no areas of the systems raised concern. There were no signs of visual damage at the time of survey in which could be deemed to influence the overall result or performance of the perlin[s] under testing in the manner indicated.

Below are the tables of results, including all measurements taken, with the observed resistance and the corresponding support moment.

C Purlin Results Table

Test Number	Length, L (m)	Height (mm)	Maximum Load (kN)	Fmax Displacement at B (mm)	Fmax Displacement at C (mm)	Fmax Displacement at D (mm)	Support Moment, M (kNm)
1	9	200	3.08	42.88	77.11	35.46	6.85
2	9	175	3.50	60.90	118.78	53.3	7.79
3	9	140	2.81	75.13	149.39	61.19	6.25
4	8	200	4.28	43.70	83.20	43.14	8.45
5	8	175	4.29	68.65	108.72	56.76	8.47
6	8	140	3.57	89.56	151.89	71.71	7.05
7	7	200	4.61	34.13	72.01	36.31	7.95
8	7	175	4.02	36.96	76.60	39.98	6.93
9	7	140	3.79	50.01	105.53	57.90	6.54
10	6	200	3.75	48.85	51.25	16.05	5.53
11	6	175	4.25	19.02	57.96	39.92	6.27
12	6	140	3.09	28.88	78.17	63.68	4.56
13	5	200	5.18	9.13	40.33	27.12	6.35
14	5	175	5.09	18.23	52.75	35.90	6.24
15	5	140	3.74	39.99	57.21	30.88	4.58
16	4	200	9.84	16.72	27.00	6.14	9.59
17	4	175	6.47	9.86	38.16	23.53	6.31
18	4	140	5.49	18.62	49.67	31.66	5.35
19	3	200	6.45	3.51	21.55	11.24	4.68
20	3	175	4.10	6.72	30.04	15.21	2.97
21	3	140	3.39	21.50	34.68	10.69	2.46
22	2	200	4.48	11.20	18.87	11.76	2.13
23	2	175	4.33	9.29	14.61	11.58	2.06
24	2	140	3.68	8.72	20.74	31.31	1.75

Table 1 – C Purlin Results

* END OF PAGE *

Z Purlin Results Table

Test Number	Length, L (m)	Height (mm)	Maximum Load (kN)	Fmax Displacement at B (mm)	Fmax Displacement at C (mm)	Fmax Displacement at D (mm)	Support Moment, M (kNm)
1	9	200	2.85	40.41	65.25	33.87	6.34
2	9	175	3.68	44.19	90.28	39.54	8.19
3	9	140	2.39	41.29	84.03	46.04	5.32
4	8	200	2.34	32.89	55.01	29.38	4.62
5	8	175	3.66	40.59	83.87	43.83	7.23
6	8	140	2.73	61.90	85.63	52.82	5.39
7	7	200	2.95	29.11	55.91	32.32	5.09
8	7	175	3.33	36.80	76.61	39.36	5.74
9	7	140	2.98	48.96	76.22	41.29	5.14
10	6	200	4.18	23.90	53.61	30.23	6.17
11	6	175	4.18	37.27	70.39	33.13	6.17
12	6	140	3.17	25.06	63.87	36.29	4.68
13	5	200	2.16	36.34	105.85	36.34	2.65
14	5	175	2.42	38.59	87.07	36.57	2.96
15	5	140	1.94	32.54	81.11	32.54	2.38
16	4	200	2.75	18.83	58.55	30.24	2.68
17	4	175	2.17	24.14	59.33	30.40	2.12
18	4	140	2.00	22.95	37.41	26.46	1.95
19	3	200	2.33	16.81	27.25	22.13	1.69
20	3	175	2.16	16.33	36.38	23.76	1.57
21	3	140	1.95	13.83	29.56	21.19	1.41
22	2	200	2.54	6.26	25.69	16.20	1.21
23	2	175	3.58	11.89	31.91	20.32	1.70
24	2	140	1.96	18.03	40.30	19.60	0.93

Table 2 – Z Purlin Results

* END OF PAGE *

C Purlin Measured Yield Table

Test Number	Length, L (m)	Height (mm)	Yield Strength (kN)
1	9	200	1.96
2	9	175	2.55
3	9	140	2.12
4	8	200	1.14
5	8	175	2.89
6	8	140	3.17
7	7	200	3.78
8	7	175	3.17
9	7	140	1.85
10	6	200	2.95
11	6	175	2.63
12	6	140	1.34
13	5	200	3.21
14	5	175	2.37
15	5	140	2.20
16	4	200	4.07
17	4	175	2.59
18	4	140	2.44
19	3	200	3.89
20	3	175	2.48
21	3	140	2.62
22	2	200	3.64
23	2	175	2.87
24	2	140	2.30

Table 3 – C Purlin Yield Results

* END OF PAGE *

Z Purlin Measured Yield Table

Test Number	Length, L (m)	Height (mm)	Yield Strength (kN)
1	9	200	0.80
2	9	175	0.56
3	9	140	0.61
4	8	200	0.73
5	8	175	0.35
6	8	140	0.32
7	7	200	1.17
8	7	175	0.98
9	7	140	0.39
10	6	200	0.83
11	6	175	0.94
12	6	140	0.91
13	5	200	1.51
14	5	175	0.67
15	5	140	0.99
16	4	200	1.76
17	4	175	1.63
18	4	140	1.42
19	3	200	1.81
20	3	175	1.37
21	3	140	1.26
22	2	200	1.51
23	2	175	1.33
24	2	140	0.91

Table 4 – Z Purlin Yield Results

* END OF PAGE *

4.0 Conclusion



After analysis of all the results. It can be said that all the tests successfully performed the loading sequence required by British Standard EN 1993-1-2:2006 and resistances, moment values and yield strength for each purlin was obtained.

Upon a brief visual survey of the purlin[s] to be tested, and post testing conclusions, there were no signs of visual damage at the time of survey in which could be deemed to influence the overall result or performance of the purlin[s] under testing in the manner indicated. All the purlins appeared to fulfil the loading sequence requirements of the British Standard EN 1993-1-2:2006, on this occasion.

This methodology provides robust compliance of proof load testing and delivers factual performance behaviour of each purlin tested.

	Name	Signature	Date
Created By: Technician	Benjamin Cartwright		12.05.2025
Checked By: Technical Director	Andrew Gore		12.05.2025

For and on behalf of Specialist Technical Services (U.K) Limited

* END OF REPORT *



Appendix A – Photographic Evidence




Figure 1 – C Purlin Failure




Figure 2 – Z Purlin Failure



Figure 3 – C Purlin Failure



Figure 4 – Z Purlin Failure



Figure 5 – Z Purlin Failure



Figure 6 – Z Purlin Failure